

REF. HI-151 FOLDING POCKET THERMOMETER



This innovative pocket thermometer is simple to switch On & Off, just fold out the built-in general purpose probe and the HI-151 switches itself on.

In use the ergonomically designed case features a convenient thumb notch to allow better grip and an LCD display conveniently located near the front of the case to provide maximum visibility and prevention of obscurity during use.

The HI -151 measures over a wide temperature range with a high degree of accuracy, all temperatures being displayed with 0.1°C resolution from -50 to +220°C. Its unique automatic calibration check every time it is used provides you the security of knowing you have consistently accurate measurements, the instrument provides a visual indication if the battery level is too low or if the thermometer requires re-calibration.

When the probe is folded away the instrument automatically switches off and is safe and convenient to carry in your pocket.

FEATURES

- Folding probe makes the CheckTemp[®] 4 smaller and easier to carry.
- Cal - Check is performed each time the meter is turned on.
- Battery ERR message when batteries need replacement.
- Auto shut-off after 8 minutes.

SPECIFICATIONS

| HI-151 Pocket Thermometer | |
|---------------------------|------------------------------------------------------------------------|
| Range | -50.0 to 220 °C |
| Resolution | 0.1° (-50 to 199.9 °C) 1° (200 to 220 °C) |
| Accuracy (@ 20°C/68°F) | ±0.4°C ± 1 digit |
| Typical EMC DEviation | ±0.3 °C |
| Calibration | Performed in factory |
| Calibration Check | Automatic at startup |
| Probe/Probe Dimensions | Stainless steel, penetration / 117 x 3.5 mm (6.75 x .187") |
| Battery Type / Life | 1 x 1.5V AA Approximately 25,000 hours (auto shut-off after 8 minutes) |
| Auto Shut-off | After 8 minutes |
| Casing | New ergonomic design |
| Dimensions | 165 x 50 x 20 mm (6.5 x 2 x 1") |
| Weight | 100 g |

Owing to continuous development. we reserve the right to introduce improvements and modify specifications without prior notice.

Sheen Instruments Ltd

Unit 4, St. Georges Ind. Est., Richmond Road, Kingston, KT2 5BQ England.

Tel: 020 8541 4333 Fax: 020 8549 3374 Intl.Tel: 44 20 8541 4333 Intl.Fax: 44 20 8549 3374